


FORM PTO-1395 (REV 11-2000)		U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE		ATTORNEY'S DOCKET NUMBER <b>2829-7</b>	
<b>TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371</b>				U.S. APPLICATION NO. (If known, see 37 C.F.R. 1.5) <b>10/019530</b> to be assigned	
INTERNATIONAL APPLICATION NO. <b>PCT/AU00/00840</b>		INTERNATIONAL FILING DATE <b>July 11, 2000</b>		PRIORITY DATE CLAIMED <b>12 July 1999</b>	
TITLE OF INVENTION <b>METHOD AND SYSTEM FOR EXCHANGING INFORMATION BETWEEN MULTIMEDIA NETWORK NODES</b>					
APPLICANT(S) FOR DO/EO/US <b>GRAF et al</b>					
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:					
1. <input checked="" type="checkbox"/> This is a <b>FIRST</b> submission of items concerning a filing under 35 U.S.C. 371. 2. <input type="checkbox"/> This is a <b>SECOND</b> or <b>SUBSEQUENT</b> submission of items concerning a filing under 35 U.S.C. 371. 3. <input checked="" type="checkbox"/> This is an express request to begin national examination procedures (35 U.S.C. 371(f)). The submission must include items (5), (6), (9) and (21) indicated below. 4. <input checked="" type="checkbox"/> The U.S. has been elected by the expiration of 19 months from the priority date (Article 31). 5. A copy of the International Application as filed (35 U.S.C. 371(c)(2)). a. <input type="checkbox"/> is attached hereto (required only if not communicated by the International Bureau). b. <input checked="" type="checkbox"/> has been communicated by the International Bureau. c. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US). 6. <input checked="" type="checkbox"/> An English language translation of the International Application as filed (35 U.S.C. 371(c)(2)). a. <input type="checkbox"/> is attached hereto. b. <input checked="" type="checkbox"/> has been previously submitted under 35 U.S.C. 154(d)(4). 7. <input type="checkbox"/> Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)). a. <input type="checkbox"/> are attached hereto (required only if not communicated by the International Bureau). b. <input type="checkbox"/> have been communicated by the International Bureau. c. <input type="checkbox"/> have not been made; however, the time limit for making such amendments has <b>NOT</b> expired. d. <input type="checkbox"/> have not been made and will not be made. 8. <input type="checkbox"/> An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)). 9. <input checked="" type="checkbox"/> An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)). 10. <input type="checkbox"/> A English language translation of the annexes of the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).  <b>Items 11 To 20 below concern document(s) or information included:</b> 11. <input checked="" type="checkbox"/> An Information Disclosure Statement under 37 C.F.R. 1.97 and 1.98. 12. <input checked="" type="checkbox"/> An assignment document for recording. A separate cover sheet in compliance with 37 C.F.R. 3.28 and 3.31 is included. 13. <input checked="" type="checkbox"/> A <b>FIRST</b> preliminary amendment. 14. <input type="checkbox"/> A <b>SECOND</b> or <b>SUBSEQUENT</b> preliminary amendment. 15. <input type="checkbox"/> A substitute specification. 16. <input type="checkbox"/> A change of power of attorney and/or address letter. 17. <input type="checkbox"/> A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821-1.825. 18. <input type="checkbox"/> A second copy of the published international application under 35 U.S.C. 154(d)(4). 19. <input type="checkbox"/> A second copy of the English language translation of the international application under 35 U.S.C. 154(d)(4). 20. <input checked="" type="checkbox"/> Other items or information. International Search Report					

U.S. APPLICATION NO. (If known, see 37 C.F.R. 1.5) <b>to be assigned 10/019530</b>		INTERNATIONAL APPLICATION NO. <b>PCT/AU00/00840</b>		ATTORNEY'S DOCKET NUMBER <b>2829-7</b>	
21. <input checked="" type="checkbox"/> The following fees are submitted:				<b>CALCULATIONS</b> PTO USE ONLY	
<b>BASIC NATIONAL FEE (37 C.F.R. 1.492(a)(1)-(5):</b> -- Neither international preliminary examination fee (37 C.F.R. 1.482) nor international search fee (37 C.F.R. 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO .....\$1040.00 -- International preliminary examination fee (37 C.F.R. 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO .....\$890.00 -- International preliminary examination fee (37 C.F.R. 1.482) not paid to USPTO but international search fee (37 C.F.R. 1.445(a)(2)) paid to USPTO .....\$740.00 -- International preliminary examination fee (37 C.F.R. 1.482) paid to USPTO but all claims did not satisfy provisions of PCT Article 33(1)-(4) .....\$710.00 -- International preliminary examination fee (37 C.F.R. 1.482) paid to USPTO and all claims satisfied provisions of PCT Article 33(1)-(4) .....\$100.00  <b>ENTER APPROPRIATE BASIC FEE AMOUNT =</b>				\$	1040.00
				\$	0.00
Surcharge of \$130.00 for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 C.F.R. 1.492(e)).				\$	0.00
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE		
Total Claims	23	-20 =	3	X \$18.00	\$ 54.00
Independent Claims	4	-3 =	1	X \$84.00	84.00
MULTIPLE DEPENDENT CLAIMS(S) (if applicable)				\$280.00	\$ 0.00
<b>TOTAL OF ABOVE CALCULATIONS =</b>				\$	<b>1178.00</b>
<input checked="" type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27. The fees indicated above are reduced by 1/2.					0.00
<b>SUBTOTAL =</b>				\$	<b>1178.00</b>
Processing fee of \$130.00, for furnishing the English Translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 C.F.R. 1.492(f)).				+	0.00
<b>TOTAL NATIONAL FEE =</b>				\$	<b>1178.00</b>
Fee for recording the enclosed assignment (37 C.F.R. 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 C.F.R. 3.28, 3.31). <b>\$40.00</b> per property				+	\$ 40.00
Fee for Petition to Revive Unintentionally Abandoned Application (\$1280.00 - Small Entity = \$640.00)				\$	0.00
<b>TOTAL FEES ENCLOSED =</b>				\$	<b>1218.00</b>
				Amount to be:	
				refunded	\$
				Charged	\$
a. <input checked="" type="checkbox"/> A check in the amount of \$1218.00 to cover the above fees is enclosed. b. <input type="checkbox"/> Please charge my Deposit Account No. 14-1140 in the amount of \$_____ to cover the above fees. A duplicate copy of this form is enclosed. c. <input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 14-1140. A duplicate copy of this form is enclosed. d. <input checked="" type="checkbox"/> The entire content of the foreign application(s), referred to in this application is/are hereby incorporated by reference in this application.					
<b>NOTE: Where an appropriate time limit under 37 C.F.R. 1.494 or 1.495 has not been met, a petition to revive (37 C.F.R. 1.137(a) or (b)) must be filed and granted to restore the application to pending status.</b>					
<b>SEND ALL CORRESPONDENCE TO:</b>  NIXON & VANDERHYE P.C. 1100 North Glebe Road, 8 <sup>th</sup> Floor Arlington, Virginia 22201-4714 Telephone: (703) 816-4000					
				 SIGNATURE	
				<b>H. Warren Burnam, Jr.</b> NAME	
29,366		January 3, 2002			
REGISTRATION NUMBER		Date			

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

In re Patent Application of

GRAF et al

Atty. Ref.: 2829-7

Serial No. to be assigned

Group: unknown

Filed: January 3, 2001

Examiner: unknown

For: METHOD AND SYSTEM FOR EXCHANGING INFORMATION BETWEEN  
MULTIMEDIA NETWORK NODES

\* \* \* \* \*

Assistant Commissioner for Patents  
Washington, DC 20231

Sir:

**PRELIMINARY AMENDMENT**

In order to place the above-identified application in better condition for examination, please amend the application as follows:

**IN THE CLAIMS**

Please substitute the following amended claims for corresponding claims previously presented. A copy of the amended claims showing current revisions is attached.

3. {AMENDED} A method as claimed in claim 1, in which the capability negotiation includes negotiation of protocol.

4. {AMENDED} A method as claimed in claim 1, wherein the multimedia information is further passed from the second network to a third network based on the first technology or a third technology, and in which the step of applying inband capability is effected to the multimedia information passing from the second to the third network.

5. {AMENDED} A method as claims in claim 1, wherein the multimedia information is user plane information, such as compressed audio stream.

8. {AMENDED} A system as claimed in claim 6, further including a third network based on the first technology or a third technology, and interface means applying TFO to the multimedia information transferred from the second to the third network.

9. {AMENDED} A system as claimed in claim 6, wherein the third network is one of a PLMN or a multimedia network.

10. {AMENDED} A system as claimed in claim 6, wherein the second network includes a plurality of telecommunication networks.

11. {AMENDED} A system as claimed in claim 6, in which the multimedia information is user plane information, such as a compressed audio stream.

12. {AMENDED} A system as claimed in claim 6, wherein the first network is a multimedia network.

13. {AMENDED} A system as claimed in claim 6, wherein the second network is a SS7 based network.

17. {AMENDED} A method as claimed in claim 15 wherein the inband signalling message conforms to the GSM Tandem Free Operation (TFO) inband signalling protocol.

19. {AMENDED} A method as claimed in claim 14 wherein the capabilities information includes information characterizing the capabilities of one or more of said nodes to transmit or receive information streams.

20. {AMENDED} A method as claimed in claim 14 wherein the operation of at least one of said first and second multimedia networks is based on ITU-T Recommendation H.323.

GRAAF et al  
Serial No. to be assigned

21. {AMENDED} A method as claimed in claim 14 wherein the operation of at least one of said first and second multimedia networks is based on the IETF RFC 2543 Session Initiation Protocol.

**REMARKS**


The above amendments are made to place the claims in a more traditional format.

Attached hereto is a marked-up version of the changes made to the claims by the current amendment. The attached page(s) is captioned "**Version With Markings To Show Changes Made.**"

Respectfully submitted,  
**NIXON & VANDERHYE P.C.**

January 3, 2002

By:



H. Warren Burnam, Jr.  
Reg. No. 29,366

HWB:lsh  
1100 North Glebe Road, 8th Floor  
Arlington, VA 22201-4714  
Telephone: (703) 816-4000  
Facsimile: (703) 816-4100

**VERSION WITH MARKINGS TO SHOW CHANGES MADE**

**IN THE CLAIMS**

3. {AMENDED} A method as claimed in claim 1 [or 2], in which the capability negotiation includes negotiation of protocol.

4. {AMENDED} A method as claimed in claim 1[, 2 or 3], wherein the multimedia information is further passed from the second network to a third network based on the first technology or a third technology, and in which the step of applying inband capability is effected to the multimedia information passing from the second to the third network.

5. {AMENDED} A method as claims in [any one of claims 1 to 4] claim 1, wherein the multimedia information is user plane information, such as compressed audio stream.

8. {AMENDED} A system as claimed in claim 6 [or 7], further including a third network based on the first technology or a third technology, and interface means applying TFO to the multimedia information transferred from the second to the third network.

9. {AMENDED} A system as claimed in claim 6[, 7 or 8], wherein the third network is one of a PLMN or a multimedia network.

10. {AMENDED} A system as claimed in [any one of claims 6 to 9] claim 6, wherein the second network includes a plurality of telecommunication networks.

11. {AMENDED} A system as claimed in [any one of claims 6 to 10] claim 6, in which the multimedia information is user plane information, such as a compressed audio stream.

12. {AMENDED} A system as claimed in [any one of claims 6 to 11] claim 6, wherein the first network is a multimedia network.

13. {AMENDED} A system as claimed in [any one of claims 6 to 12] claim 6, wherein the second network is a SS7 based network.

17. {AMENDED} A method as claimed in claim 15 [or 16] wherein the inband signalling message conforms to the GSM Tandem Free Operation (TFO) inband signalling protocol.

19. {AMENDED} A method as claimed in [any of claims 14 to 18] claim 14 wherein the capabilities information includes information [characterising] characterizing the capabilities of one or more of said nodes to transmit or receive information streams.

20. {AMENDED} A method as claimed in [any of claims 14 to 19] claim 14 wherein the operation of at least one of said first and second multimedia networks is based on ITU-T Recommendation H.323.

21. {AMENDED} A method as claimed in [any of claims 14 to 20] claim 14 wherein the operation of at least one of said first and second multimedia networks is based on the IETF RFC 2543 Session Initiation Protocol.

**METHOD AND SYSTEM FOR EXCHANGING INFORMATION BETWEEN  
MULTIMEDIA NETWORK NODES**

**FIELD OF INVENTION**

The present invention relates to the interworking of networks, particularly to  
5 the interworking of information through telecommunication networks. In one form,  
the present invention relates to the interworking of multimedia networks and  
telecommunication networks based on SS7 Common Channel Signalling.

The present invention relates generally to the transmission of video, audio  
and/or data signals between nodes in multimedia networks, and in particular to  
10 the exchange of control information, in the form of capabilities information,  
between such nodes. The invention is suitable for use in the negotiation of the  
capabilities of nodes, notably in H.323 and SIP multimedia networks, to transmit  
out-going information streams and receive and process in-coming information  
streams, and it will be convenient to hereinafter describe the invention in relation  
15 to that exemplary application. It is to be appreciated, however, that the invention  
is not limited to use in that application, only.

**BACKGROUND OF INVENTION**

Multimedia networks are networks such as those based on H.323, ITU-T  
H.323, Packet Based Multimedia Communication Systems, and SIP, IETF RFC  
20 2543 Session Initiation Protocol, and have the ability to negotiate capabilities  
between nodes.

In the context of the present specification, the expression "nodes" is  
intended to refer to endpoint terminals for receiving and transmitting user  
information, this also includes network nodes and servers which handle the  
25 switching of such information in the network and gateways between adjacent  
networks. The capability exchange procedures of multimedia networks are  
intended to ensure that the only multimedia signals to be transmitted are those  
which can be received and treated appropriately by the receiving node, by making  
the capabilities of each node to transmit, receive and decode information streams  
30 known to the other node or nodes.

H.323 multimedia networks therefor use a protocol called H.245, ITU-T  
H.245, Control Protocol for Multimedia Communication, which uses

10019530-010302



OpenLogicalChannel and / or TerminalCapability messages / structures to exchange information between H.323 endpoints or nodes about the capabilities supported by the nodes.

Similarly, SIP (Session Initiation Protocol) is defined by the Internet Engineering Task Force (IETF). Part of the SIP multimedia architecture is the Session description protocol (SDP), IETF RFC 2327 Session Description Protocol. It is used to negotiate a set of capabilities between SIP endpoints or nodes (SIP server, SIP client etc).

The following is an example of the capabilities information that is able to be negotiated by multimedia negotiation protocols:

Audio (define type and direction - send, receive, send & receive)  
Video (define type and direction - send, receive, send & receive)  
Data (define type and direction - send, receive, send & receive)  
Encryption  
Conference  
Security

Once this negotiation has taken place the user data is transported between the nodes in the format specified by this negotiation. This negotiation can take place at any time. For example, call setup, within an established session etc.

Another example of negotiation between nodes, but which differs from the above multimedia negotiation, is in modern communication networks which include mobile nodes or endpoints. Figure 1 illustrates a communication system including third generation Public Land Mobile Networks (PLMNs) 12, 14 and also a fixed transit network (PSTN/ISDN) 13. The PLMNs 12, 14 are capable of operating with compressed voice streams in their core networks. This is voice stream coding which is asynchronous or synchronous in nature, and transmitted and / or received at bit rates in the range typically of 8 - 16 kbit/s. In discussing the transmission of the compressed voice streams between mobile nodes, we have now turned our attention, for the purposes of illustrating the prior art, to the lower physical and access layer protocols unrelated to the higher layer protocols of the multimedia networks discussed above.

PSTN/ISDN networks 13 usually operate with synchronous 64kbit/s PCM coded voice streams, which occupies a 64kbit/s time slot. If a call originating in a PLMN 12, 14 traverses a PSTN/ISDN network 13, in other words, the voice stream passes from a PLMN network 12 to a PSTN/ISDN network 13, to a terminating  
5 PLMN 14, the voice stream is transcoded from its compressed format to a synchronous PCM coded format and then again transcoded back to its compressed format. This is because there is no ability to negotiate or signal the use of another codec type or bandwidth through the PSTN/ISDN or SS7 based network 13. This is exemplified in Figure 1, where the PSTN/ISDN network 13 is unable to allow an  
10 indication of GSM AMR and thus a default PCM coding is required. Transcoding is then necessary. Flowing from this, any gains in bandwidth efficiency on the mobile side are lost because the use of transcoding between codec formats reduces the quality of the original user data. Transcoding should thus be avoided where possible.

15 With the introduction of Mobile telecommunications networks compressed voice was brought to the edge of the 'fixed' telecommunications networks. The user plane data in a mobile network is encoded by codecs producing compressed voice. For example: GSM AMR and EFR coding. As a result, a smaller 'pipe' supporting less bandwidth is needed.

20 The result is that, a network given the same amount of bandwidth can handle more calls.

However, when a fixed telecommunications network interfaces with a mobile network, the compressed voice must be transcoded from the compressed format to the PCM format of the fixed network.

25 To alleviate the problem of codec negotiation between mobile nodes where calls traverse a PSTN/ISDN network a solution has been posed where in band signalling is used to negotiate codecs when interfacing PSTN/ISDN networks based on SS7 technology. A developed protocol called Tandem Free Operation TFO, ETSI GSM 08.62 allows mobile network nodes to signal and negotiate the type of  
30 codec and thus the bandwidth through the network(s) via in band communication. This also alleviated the need for transcoding which would lead to the degradation of quality of the original user plane data.

Nonetheless, there is still a problem as yet unresolved of when Multimedia networks (e.g. H.323 and SIP) are interfaced with a Telecommunications networks based on SS7 in that they experience a similar problem as that associated with mobile networks separated by a PCM network as described above and in that, unlike mobile/PCM network interfaces that cannot negotiate codecs, the multimedia networks cannot negotiate capabilities between nodes when sessions traverse PCM networks.

For example, the information signalled in the multimedia compatibility protocols such as H.323 and SDP is lost because the SS7 protocols cannot carry this information. As such a node / server / gateway / media gateway is forced to transcode the user data leading to a degradation in quality.

Another deficiency in prior art systems arises where the amount of capabilities information required to be transmitted in the negotiations for multimedia sessions is too large for the TFO frames that convey codec information in mobile/fixed network interfaces.

Although in the case of PLMN/PCM network interfaces the TFO solution has allowed the negotiation of codecs, it has been found that the present form of the in band codec negotiation in PLMN/PCM interfaces does not cater for the type and amount of information required to be transported for negotiating capabilities of multimedia nodes in sessions across a PSTN/ISDN PCM network.

It is an object of the invention to provide a method and system for exchanging capabilities information between nodes in multimedia networks across a fixed or switched telecommunications network which ameliorates or overcomes one or more disadvantages of the prior art.

It is a further object of the invention to enable nodes in multimedia networks to exchange capabilities information across a fixed or switched telecommunications network.

#### SUMMARY OF INVENTION

The present invention provides a method of enabling multimedia information to pass between a first network based on a first technology and a second network based on a second technology, by enabling the first and / or second networks to apply a method of inband capability negotiation or signalling including logically

mapping multimedia capabilities information to in band messages in order to establish the format for the passing of the multimedia information from the first network to the second network.

Preferably, the inband messages are TFO (Tandem Free Operation) messages.

Preferably, the multimedia information is further passed from the second network to a third network based on the first technology or a third technology, and in which the step of applying inband capability negotiation is effected to the multimedia information passing from the second to the third network.

Preferably, the multimedia information is user plane information, such as compressed audio stream.

The present invention also provides a communication system having a first network based on a first technology, a second network based on a second technology, and interface means enabling the first and second networks to apply an inband methodology including logically mapping multimedia capabilities information to in band messages in order to signal and / or negotiate the passing of multimedia information from the first network to the second network.

Preferably, the inband messages are TFO (Tandem Free Operation) messages.

Preferably, the system further includes a third network based on the first technology or a third technology, and interface means applying TFO to the multimedia capabilities information transferred from the second to the third network.

Preferably, the networks may be one or more of PLMN network, multimedia network or SS7 based network.

In essence, having realised that the problem lies in the present form of in band codec negotiation for mobile/fixed SS7 network interfaces being unsuitable for negotiating capabilities of multimedia sessions across fixed SS7 networks, the invention stems from addressing this by logically mapping multimedia capabilities information to in band messages. The messages, in turn, provide communication channels for conveying capabilities information inside a multimedia path between respective nodes. One step in the present invention was realising that existing TFO

frame sizes and structures were not large enough to transport all the information needed for multimedia network capabilities negotiation.

In other words, the present invention overcomes the disadvantages of the prior art use of the TFO protocol by logically mapping the multimedia capabilities information to existing in band messages. By "logically mapping" we mean mapping the multimedia capabilities information to a TFO message format and then embedding the TFO message in successive TFO frames and/or existing PCM samples of one or more 64 kBits/sec links in the PSTN/ISDN network by bit stealing from the successive frames and/or PCM samples.

As TFO provides a means of inband capability negotiation when interfacing with mobile networks, the present invention, in one preferred form, seeks to extend the use of TFO to the interface between multimedia networks (i.e. H.323, SIP) and Telecommunications based on SS7.

Throughout this specification, by 'information' we mean data, voice, video and / or any other form of information electronically transmissible. A preferred form of the invention relates to the transmission of audio or voice streams.

In this specification, a multimedia network is a network that through the use of Call / Session control and / or capability negotiation allows for the control and transport of different types of media, including but not limited to, audio, video, data or different types of transport in data, fixed and mobile. For example H.323, , SIP based multimedia networks.

In one form, the present invention can reside in an interface between a multimedia network and a traditional telecommunications network which uses inband signalling.

One aspect of the present invention provides a method for exchanging capabilities information between a first node in a first multimedia network and a second node in a second multimedia network, said first and second multimedia networks being separated by a fixed or switched telecommunications transit network across which capabilities information between said first and second nodes is transported, the method including the steps of:

transmitting from said first multimedia network to said fixed or switched telecommunications network a control message containing capabilities information intended to govern the operation of said second node,

at the interface between said first multimedia network and said fixed or  
5 switched telecommunications network, mapping said capabilities information into an inband signalling message for transport in a bearer channel within said fixed or switched telecommunications network, and

at the interface between said fixed or switched telecommunications network and said second multimedia network, removing said capabilities  
10 information from within said inband signalling message for transmission to said second node.

In this way, the exchange of control messages between nodes in the first and second multimedia networks, which enable notably the end-to-end negotiation of capabilities, is able to be carried out through traditional  
15 telecommunications networks, such as those based on SS7 and new telecommunications networks based on call control not being tied to underlying user plane transport, such as the Bearer Independent Call Control (BICC) network. The use of transcoders can thus be eliminated, resulting in better speech quality and more efficient use of resources in the networks.

20 Preferably, the inband signalling message conforms to the GSM Tandem Free Operation (TFO) inband signalling protocol. The inband signalling message may be a TFO Message.

In one embodiment, the capabilities information includes information characterising the capabilities of one or more of said nodes to transmit or receive  
25 information streams.

The operation of at least one of said first and second multimedia networks may be based on ITU-T Recommendation H.323. Alternatively, the operation of at least one of said first and second multimedia networks may be based on the IETF  
RFC 2543 Session Initiation Protocol.

30 The operation of the fixed or switched telecommunications network may be based on the ITU-T Signalling System No. 7 Recommendation.

10019530-010302

Another aspect of the invention provides a system for exchanging capabilities information between a first node in a first multimedia network and a second node in a second multimedia network, said first and second multimedia networks being separated by a fixed or switched telecommunications transit network across which capabilities information between said first and second nodes is transported, the system including:

means for transmitting a control message containing capabilities information, intended to govern the operation of said second node, from said first multimedia network to said fixed or switched telecommunications network,

means for mapping said capabilities information, at an interface between said first multimedia network and said fixed or switched telecommunications network, into an inband signalling message for transport in a bearer channel within said fixed or switched telecommunications network, and

means for removing said capabilities information, at the interface between said fixed or switched telecommunications network and said second multimedia network, from within said inband signalling message for transmission to said second node.

The capabilities information mapping and removing means may be provided by one or more gateways, media gateways, rate adaptor units or interworking units interconnecting said first and second multimedia networks to said fixed or switched telecommunications network.

The following description refers in more detail to the various features of the present invention. To facilitate an understanding of the invention, reference is made in the description to the accompanying drawings where the method and system of exchanging capabilities information between nodes in multimedia networks is illustrated in a preferred embodiment. It is to be understood that the invention is not limited to this preferred embodiment.

In the drawings:

Figure 1 is a schematic diagram of two PLMN mobile networks, which are interconnected by a PSTN/ISDN fixed transit network;

Figure 2 is a schematic diagram of two multimedia networks, based respectively on the H.323 and SIP standards, which are interconnected by a PSTN/ISDN transit network;

Figure 3 illustrates a TFO frame used to transport user information from one multimedia network in Figure 2 to the other across the PSTN/ISDN transit network;

Figure 4 illustrates the insertion of the TFO frame of Figure 3 into 8 bit PCM samples transmitted in the PSTN/ISDN network of Figure 2;

Figure 5 illustrates a TFO message used for the inband signalling of capabilities information from one multimedia network in Figure 2 to the other across the PSTN/ISDN transit network; and

Figure 6 illustrates part of the capabilities negotiation process between endpoints in the two multimedia networks of Figure 2 across the PSTN/ISDN network.

Referring now to Figure 2, there is shown generally a telecommunications system 200 including a first multimedia network 22, a second multimedia network 23 and a PSTN/ISDN network 24. The PSTN/ISDN network 24 is a switched network developed for the transmission of voice traffic, whereas both multimedia networks 22 and 23 are designed for the transmission of video, audio and data information streams between nodes 25, 27 within each network rather than to generally support telephone services. It is to be understood that the operation of multimedia networks 22 and 23 may be based upon the same or different recommendations or modes of operation.

In this example, the operation of the first multimedia network 22 is based upon ITU-T Recommendation H.323, which describes terminals, equipment and services for multimedia communications (voice, video and data) over Local Area Networks (LANs/WANs) which may provide guaranteed Quality of Service (QoS). The H.323 network 22 includes a plurality of H.323 terminals, such as that referenced 25 in Figure 1. The H.323 terminal 25 is an endpoint on the local area network 22 which provides for real-time, two way communications with another H.323 terminal, Gateway, or Multipoint Control Unit. This communication consists of control, indications, audio, moving colour video pictures, and/or data between



the two of the aforementioned network nodes 25, 27. A node may provide speech only, speech and data, speech and video, or speech, data and video. An H.323 Gateway 26 is provided as an endpoint on the local area network 26, and provides for real-time, two-way communication between the H.323 terminals on the LAN 26 and other ITU nodes forming part of the ISDN/PSTN network 24.

Similarly, the SIP multimedia network 23 includes a plurality of SIP terminals, such as that referenced 27 in Figure 1. The SIP terminal 27 is an endpoint within the SIP network 23. The SIP Protocol is an application-layer control (signalling) protocol which enables the creation, modification and termination of sessions between one or more nodes within the SIP network 23. These sessions include multimedia conferences, Internet telephone calls and multimedia distribution. A SIP Gateway 28 interconnects the SIP network 23 and the PSTN/ISDN network 24 in order to enable real-time, two-way communication between the SIP terminals in the SIP network 23 and ITU nodes forming part of the ISDN/PSTN network 24.

Terminals within the H.323 network 22 use the ITU-T Recommendation H.245 to exchange information messages as well as procedures to use them for inband negotiation at the start or during communication between two or more such terminals. The messages cover receiving and transmitting capabilities as well as mode preference from the receiving terminal, logical channel signalling, and Control and Indication. Acknowledged signalling procedures are specified to ensure reliable audiovisual and data communication. H.245 information is exchanged between H.323 terminals on a control channel established for the duration of the communication between the terminals.

Terminals within the SIP network 23 use SDP to exchange similar information messages. SDP describes multimedia sessions between two or more terminals and is used to convey session announcement, session invitation and other forms of multimedia session initiation. A common mode of usage is for a multimedia session to be announced by the periodic multicasting of an announcement packet, which consists of a Session Announcement Protocol (SAP) header and text payload describing the multimedia session.

User information is conveyed in the PSTN/ISDN network 24 in 64 kBits/sec links. However, in order to enable one or more nodes in the H.323 network 22 to exchange multimedia information with one or more nodes in the SIP network 23, capabilities information intended to govern the operation of one or more of such nodes during a multimedia session is transported across the network 24 as an inband signalling message within the 64 kBits/sec link. The inband signalling message may conform to the GSM TFO inband signalling protocol. Although this protocol was developed to enable mobile-to-mobile calls to be made in GSM networks without requiring tandem coding to be carried out on the speech signal, it has surprisingly been found to be suitable for use in the context of the present invention.

Multimedia voice, audio and/or data signals are transported across the PSTN/ISDN network 24 in TFO Frames, an example of which is shown in Figure 3. TFO Frames have a fixed size and length depending on the codec used by the endpoints in each of the multimedia networks 22 and 23. In the TFO Frame 10 of Figure 3, the frame length is 320 bits. The TFO frame 10 includes synchronisation bits in the first two octets, and 21 control bits C1 to C21 which enclose the information payload borne by the Frame. It will be appreciated that the Frame structure shown in this Figure is illustrative only, and that various other Frame structures may be easily conceived by a skilled person in the telecommunications field.

The TFO Frame 10 may be carried by a channel mapped onto one or more bits of the PCM samples of one or more 64 kBits/sec links in the PSTN/ISDN network 24. The number of bits occupied will depend upon the transmission rate of the multimedia information stream transported across the PSTN/ISDN network 24. For example, if the multimedia information stream is transported at a rate of 16 kBits/sec, the TFO Frame 10 may be mapped onto the two least significant bits of the PCM samples, as shown by the PCM sample stream 20 represented in Figure 4.

TFO Messages are transmitted on the same 64 kBits/sec link prior and parallel to the TFO Frames. TFO Messages, an example of which is shown in Figure 5, provide communication channels for conveying capabilities information

inside the multimedia information path between respective endpoints in the multimedia networks 22 and 23. The TFO message 30 of Figure 5 includes a header, a command block and possibly one or more extension blocks. The header, in this example, consists of a 20-bit long sequence H1 to H18 (including two "0" bits). The command block, referenced CB1 to CB200, identifies the capabilities information sent between multimedia nodes across the PSTN/ISDN network 24. Extension blocks, here referenced E1 to E20, extend the size of the command block of the TFO message 30.

The TFO message 30 may be transported on the 64 kBits/sec link by being sent together with (embedded into) a TFO Frame 10, or by being inserted into the PCM sample stream 20. In this latter case, the TFO Message 30 may be transferred within the LSB of the PCM sample stream 20 by replacing every 16<sup>th</sup> consecutive PCM sample with one bit of the TFO Message.

An example of the exchanging of capabilities information between the H.323 endpoint 25 in the H.323 network 22 and the SIP endpoint 27 in the SIP network 23 will now be described with reference to Figure 6. Prior to the establishment of a multimedia session between the endpoints 25 and 27, the endpoint 25 may act to ensure that the endpoint 27 is able to receive and appropriately process the video, audio and/or data information stream it intends transmitting to the endpoint 27. In this case, the endpoint 25 transmits a TerminalCapabilitySet 40 containing information about its capability to transmit and receive. The TerminalCapabilitySet 40 includes a sequenceNumber to label the particular instance of the TerminalCapabilitySet so that a corresponding response from the endpoint 27 can be identified, a protocolIdentifier to indicate the version of the H.245 Recommendation in use, and a CapabilityTableEntry describing, in this case, the capability of the endpoint 25 to send and receive audio using G.723.1 encryption.

The TerminalCapabilitySet 40 is conveyed across the H.323 network 22 to the H.323 gateway 26, which acts to map the TerminalCapabilitySet 40 into a TFO Message 41. The TFO Message 41 has the structure TFO\_REQ\_L (Codec G7231), indicating that the source of the message is a TFO capable device and that the G.723.1 Audio Codec is the codec used at the endpoint 25. The TFO

Message 41 is then transmitted as an inband message within a 64 kBits/sec link across the PSTN/ISDN network 24.

Upon receipt by the SIP Gateway 28, the information contained in the TFO Message 41 is removed and mapped into a SAP Message 42. Accordingly, the  
5 protocol version, OwnerSessionID, SessionName and ConnectionInformation are created and placed in a SAP message intended for the endpoint 27. Moreover, information from the TFO Message 41 is able to be mapped into the TimeSessionActive field, the SessionDescription field - sendrecv (corresponding to the receiveAndTransmitAudioCapability transmitted in the H.245 Message 40) -  
10 and the MediaAnnoucements field - Audio PORT Transport G7231 (corresponding to the G7231 Audio transmitted in the H.245 Message 40).

The present invention allows for the end to end negotiation of capabilities through traditional telecommunication networks based on SS7 and new telecommunications networks based on Bearer Independent Call Control (BICC).  
15 Those skilled in the art will appreciate that there may be many other variations, modifications and/or additions to the configuration described herein which are within the scope of the present invention.

10019530-010103  
2000-07-07

## THE CLAIMS DEFINING THE INVENTION ARE AS FOLLOWS:

1. A method of enabling multimedia information to pass between a first network based on a first technology and a second network based on a second technology, the method including the step of:  
enabling the first and / or second networks to apply a method of inband capability negotiation or signalling including logically mapping multimedia capabilities information to in band messages in order to establish the format for the passing of the multimedia information from the first network to the second network.
2. A method as claimed in claim 1, wherein the inband messages are TFO (Tandem Free Operation) messages.
3. A method as claimed in claim 1 or 2, in which the capability negotiation includes negotiation of protocol.
4. A method as claimed in claim 1, 2 or 3, wherein the multimedia information is further passed from the second network to a third network based on the first technology or a third technology, and in which the step of applying inband capability is effected to the multimedia information passing from the second to the third network.
5. A method as claimed in any one of claims 1 to 4, wherein the multimedia information is user plane information, such as compressed audio stream.
6. A communication system having  
a first network based on a first technology,  
a second network based on a second technology, and  
interface means enabling the first and second networks to apply an in band methodology including logically mapping multimedia capabilities information to in band messages in order to signal and / or negotiate the passing of multimedia information from the first network to the second network.

7. A system as claimed in claim 6, wherein the in band messages are TFO (Tandem Free Operation) messages.
8. A system as claimed in claim 6 or 7, further including a third network based on the first technology or a third technology, and interface means applying TFO to the multimedia information transferred from the second to the third network.
9. A system as claimed in claim 6, 7 or 8, wherein the third network is one of a PLMN or a multimedia network.
10. A system as claimed in any one of claims 6 to 9, wherein the second network includes a plurality of telecommunication networks.
11. A system as claimed in any one of claims 6 to 10, in which the multimedia information is user plane information, such as a compressed audio stream.
12. A system as claimed in any one of claims 6 to 11, wherein the first network is a multimedia network.
13. A system as claimed in any one of claims 6 to 12, wherein the second network is a SS7 based network.
14. A method for exchanging capabilities information between a first node in a first multimedia network and a second node in a second multimedia network, said first and second multimedia networks being separated by a fixed or switched telecommunications transit network across which capabilities information between said first and second nodes is transported, the method including the steps of:
  - transmitting from said first multimedia network to said fixed or switched telecommunications network a control message containing capabilities information intended to govern the operation of said second node,
  - at the interface between said first multimedia network and said fixed or switched telecommunications network, mapping said capabilities information into

an inband signalling message for transport in a bearer channel within said fixed or switched telecommunications network, and

at the interface between said fixed or switched telecommunications network and said second multimedia network, removing said capabilities information from within said inband signalling message for transmission to said second node.

15. A method as claimed in claim 14 wherein the fixed or switched telecommunications network is based on SS7.

16. A method as claimed in claim 14 wherein the fixed or switched telecommunications network is based on call control not being tied to underlying user plane transport, such as a Bearer Independent Call Control (BICC) network.

17. A method as claimed in 15 or 16 wherein the inband signalling message conforms to the GSM Tandem Free Operation (TFO) inband signalling protocol.

18. A method as claimed in claim 17 wherein the inband signalling message is a TFO Message.

19. A method as claimed in any of claims 14 to 18 wherein the capabilities information includes information characterising the capabilities of one or more of said nodes to transmit or receive information streams.

20. A method as claimed in any of claims 14 to 19 wherein the operation of at least one of said first and second multimedia networks is based on ITU-T Recommendation H.323.

21. A method as claimed in any of claims 14 to 20 wherein the operation of at least one of said first and second multimedia networks is based on the IETF RFC 2543 Session Initiation Protocol.

10019530.0103002


means for mapping said capabilities information, at an interface between said first multimedia network and said fixed or switched telecommunications network, into an inband signalling message for transport in a bearer channel within said fixed or switched telecommunications network, and

means for removing said capabilities information, at the interface between said fixed or switched telecommunications network and said second multimedia network, from within said inband signalling message for transmission to said second node.

23. A system as claimed in claim 22 wherein the capabilities information mapping and removing means is provided by one or more gateways, media gateways, rate adaptor units or interworking units interconnecting said first and second multimedia networks to said fixed or switched telecommunications network.




Fig 1.  
(Prior Art)



2/6

Fig 2.



3/6


Fig 3.

10

TFO FRAME

OCTET NUMBER	BIT NUMBER							
	1	2	3	4	5	6	7	8
0	0	0	0	0	0	0	0	0
1	0	0	0	0	0	0	0	0
2	1	C1	C2	C3	C4	C5	C6	C7
3	C8	C9	C10	C11	C12	C13	C14	C15
4								
5								
6								
7								
8								
9								
10								
11								
12								
13								
14								
15								
16								
17								
18								
19								
20								
21								
22								
23								
24								
25								
26								
27								
28								
29								
30								
31								
32								
33								
34								
35								
36								
37								
38							C16	C17
39	C18	C19	C20	C21	T1	T2	T3	T4

Fig. 4.



5/6

Fig 5.

30

TFO MESSAGE

OCTET NUMBER	BIT NUMBER							
	1	2	3	4	5	6	7	8
0	0	H1	H2	H3	H4	H5	H6	H7
1	H8	H9	0	H10	H11	H12	H13	H14
2	H15	H16	H17	H18	CB1	CB2	CB3	.....
3								
4								
5								
6								
7								
8								
9								
10								
24								
25								
26								
27								
28								
29								
30						.....	CB199	CB200
31	E1	E2	E3	E4	E5	E6	E7	E8
32	E9	E10	E11	E12	E13	E14	E15	E16
33	E17	E18	E19	E20				
34								
35								
36								

6/6

Fig 6.

Example: Mapping between H.245, TFO & SDP

H.245 TerminalCapabilitySet

TerminalCapabilitySet  
{sequenceNumber  
protocolIdentifier  
capabilityTableSequenceNumber,  
OBJECT IDENTIFIER,  
CapabilityTableEntry  
CapabilityTableEntryNumber,  
Capability  
receiveAndTransmitAudio Capability  
G.723.1

40

maps to:

TFO

TFO\_REQ\_L(Codec G.723.1 )

41

maps to:

SDP

v=0

o= Owner SessionID

s=SessionName

c=Connectioninformation

t=Time session active

a=sendrecv

m=AudioPort Transport G.723.1

42

RULE 63 (37 C.F.R. 1.63)  
DECLARATION AND POWER OF ATTORNEY  
FOR PATENT APPLICATION  
IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

As a below named inventor, I hereby declare that my residence, post office address and citizenship are as stated below next to my name, and I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

Method and System for Exchanging Information Between Multimedia Network Nodes

the specification of which (check applicable box(es)):

☐ Is attached hereto

☐ was filed on

as U.S. Application Serial No.

(Atty Dkt. No. 100-40)

☒ was filed as PCT International application No. PCT/AU00/00840

on July 11th, 2000

and (if applicable to U.S. or PCT application) was amended on

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above. I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with 37 C.F.R. 1.56. I hereby claim foreign priority benefits under 35 U.S.C. 119/365 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed or, if no priority is claimed, before the filing date of this application:

Priority Foreign Application(s):

Application Number

Country

Day/Month/Year Filed

PQ1564 & PQ1625

Australia

on 12th July, 1999 & 14th July, 1999

I hereby claim the benefit under 35 U.S.C. §119(e) of any United States provisional application(s) listed below.

Application Number

Date/Month/Year Filed

I hereby claim the benefit under 35 U.S.C. 120/365 of all prior United States and PCT international applications listed above or below and, insofar as the subject matter of each of the claims of this application is not disclosed in such prior applications in the manner provided by the first paragraph of 35 U.S.C. 112, I acknowledge the duty to disclose material information as defined in 37 C.F.R. 1.56 which occurred between the filing date of the prior applications and the national or PCT International filing date of this application:

Prior U.S./PCT Application(s):

Application Serial No.

Day/Month/Year Filed

Status: patented

pending, abandoned

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true, and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon. And I hereby appoint NIXON & VANDERHYE P.C., 1100 North Glebe Rd., 8th Floor, Arlington, VA 22201-4714, telephone number (703) 816-4000 (to whom all communications are to be directed), and the following attorneys thereof (of the same address) individually and collectively my attorneys to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith and with the resulting patent: Arthur R. Crawford, 25327; Larry S. Nixon, 25640; Robert A. Vanderhye, 27076; James T. Hosmer, 30184; Robert W. Faris, 31352; Richard G. Besha, 22770; Mark E. Nusbaum, 32348; Michael J. Keenan, 32106; Bryan H. Davidson, 30251; Stanley C. Spooner, 27393; Leonard C. Mitchard, 29009; Duane M. Byers, 33363; Jeffrey H. Nelson, 30481; John R. Lastova, 33149; H. Warren Burnam, Jr., 29366; Thomas E. Byrne, 32205; Mary J. Wilson, 32955; J. Scott Davidson, 33489; Alan M. Kagen, 36178; William J. Griffin, 31260; Robert A. Molan, 29834; B. J. Sadoff, 36663; James D. Berquist, 34776; Updeep S. Gill, 37334; Michael J. Shea, 34725; Donald L. Jackson, 41090.

1. Inventor's Signature: [Signature] Date: 14 November, 2001  
Inventor: Leslie Graf MI Graf Australia  
(first) (last) (citizenship)  
Residence (city): Victoria Aux (state/country) Australia  
Post Office Address: 3 Hender Court, Balwyn, Victoria 3103, Australia.  
(Zip Code) 3103

2. Inventor's Signature: [Signature] Date: 16 November 2001  
Inventor: Christian Norman Groves Australia  
(first) (last) (citizenship)  
Residence (city): Victoria Aux (state/country) Australia  
Post Office Address: 21 Garden Avenue, Keilor, Victoria 3036, Australia  
(Zip Code) 3036

315933

300

Inventor's Signature:

Inventor:

Residence: (city)

Post Office Address:  
(Zip Code)

X Mark Hollis  
Mark Hollis  
Victoria AU  
3114

Date: 20th November, 2001

Australia  
(citizenship)

(state/country) Australia

1 Daintree Avenue, Park Orchards, Victoria 3114, Australia.  
3114.

400

Inventor's Signature:

Inventor:

Residence: (city)

Post Office Address:  
(Zip Code)

X Juan Noguera-Rodriguez  
Juan Noguera-Rodriguez  
Victoria AU  
3040

Date: 12 November, 2001

Spanish  
(citizenship)

(state/country) Australia

348 Deakin Street, Essendon, Victoria 3040, Australia  
3040.

500

Inventor's Signature:

Inventor:

Residence: (city)

Post Office Address:  
(Zip Code)

Stephen C Terrill  
Stephen Christopher Terrill  
Stockholm SE  
Hamacker, -Flemingatan 45, 4tr, Stockholm, Sweden

Date: 30 October, 2001

Australia  
(citizenship)

(state/country) Sweden

Inventor's Signature:

Inventor:

Residence: (city)

Post Office Address:  
(Zip Code)

Victoria

(last)  
(state/country) Australia

Australia  
(citizenship)

Inventor's Signature:

Inventor:

Residence: (city)

Post Office Address:  
(Zip Code)

Victoria

(last)  
(state/country) Australia

Australia  
(citizenship)

Inventor's Signature:

Inventor:

Residence: (city)

Post Office Address:  
(Zip Code)

Victoria

(last)  
(state/country) Australia

Australia  
(citizenship)